

# Bookeye® 5

## Bookeye® 5 V1A Professional



### Scanning Speed

The scanning speed depends on the resolution alone. The Bookeye® 5 scanner always scans in full color, even if bitonal image output is selected. This produces the best possible images. The following matrix shows the scan speed depending on the resolution.

#### BE5-V1A Professional Scan Time A1+ (914\*635 mm)

DIN A1+	@ 150 dpi	1.2 s
DIN A1+	@ 200 dpi	1.5 s
DIN A1+	@ 300 dpi	2.1 s
DIN A1+	@ 400 dpi	2.8 s
DIN A1+	@ 600 dpi	4.1 s

## Optical System

Maximum Scan Area	635 x 914 mm (25 x 36 inch), 16% more than DIN/ISO A1
Scanner Resolution	600 x 600 dpi
Pixel Dimension	9.3 x 9.3 µm
Minimum Document Size	100 x 100 mm (4 x 4 inch)
Camera	CCD line sensor, 22,500 pixels (11,000 scan lines equals to a 245 MPixel matrix camera)
Live Preview Camera	CMOS matrix, area sensor
Color Depth	48 bit color 16 bit grayscale
Scan Modes	24 bit color, 8 bit grayscale, bitonal, enhanced halftone
File Formats	Multipage PDF (PDF/A) and TIFF, JPEG, JPEG 2000, PNM, PNG, BMP, TIFF (Raw, G3, G4, LZW, JPEG), AutoCAD DWF, JBIG, DjVu, DICOM, PCX, Postscript, EPS, Raw data and more

## Illumination System

Light Source	White LEDs, tested according to IEC 62471
Warm-up Time	None
Temperature Dependency	None
UV / IR Emission	None
Lamp Lifetime	50,000 hours typ. Lamps are covered by the Extended Warranty Option

## Electrical Specifications

### Two External Power Supplies

Voltage	100 – 240 V AC
Frequency	47 – 63 Hz
Operating Temperature	5 to 40 °C (40 to 105 °F)
Relative Humidity	20 to 80% (non-condensing)
ECO Standard	CEC level VI

### Scanner

Voltage	24 V DC
Current	Max. 7.5 A

### Power Consumption

$P_{(Off)}$	0.3W
$P_{(Sleep)}$	5.4W
$P_{(Ready)}$	120W
$P_{(Active)}$	200W

33% below [ENERGY STAR requirements](#)

[Image Access FAQ](#)

## Document Specifications

Maximum Book Weight	30 kg (65 lbs.)
---------------------	-----------------

## Dimensions and Weight

Scanner Outer Dimensions (H x W x D)	1160 x 900 x 900 mm (46 x 35 x 35 inch)
Scanner outer dimensions, book cradle opened (H x W x D)	1160 x 1085 x 900 mm (46 x 43 x 35 inch)
Weight of Scanner	90 kg (200 lbs.)
Dimension Transport Box (H x W x D)	740 x 1000 x 1200 mm (29 x 39 x 47 inch)
Scanner Weight, Ready to Ship	150 kg (331 lbs.)

## Ambient Conditions

Operating Temperature	5 to 40 °C (40 to 105 °F)
Storage Temperature	0 to 60 °C (32 to 140 °F)
Relative Humidity	20 to 80% (non-condensing)
Ambient Luminance	< 800 Lux
Noise	< 48 dB(A) (Lift & opening motors) < 42 dB(A) (Operating) < 33 dB(A) (Standby)

© 2023 by Image Access GmbH, Wuppertal, Germany.

Printed in Germany. All rights reserved. Reproduction in whole or in part in any form or medium without express written permission of Image Access is prohibited. Scan2Net®, Scan2Pad®, WideTEK® and Bookeye® are registered trademarks of Image Access. All other trademarks are the property of their respective owners.

Image Access reserves the right to change the described products, the specifications or documents at any time without prior notice. For the most recent version, always check our web site [www.imageaccess.de](http://www.imageaccess.de) or [www.imageaccess.us](http://www.imageaccess.us) or the customer service portal at [portal.imageaccess.de](http://portal.imageaccess.de)